

PROCESS

Note: This statement is only available with Entire System Server.

PROCESS *view-name* **USING** *operand1* = *operand2* **GIVING** *operand3* ...

Operand	Possible Structure					Possible Formats										Referencing Permitted	Dynamic Definition
Operand1	C	S				A	N	P		B						yes	no
Operand2	C	S				A	N	P		B						yes	no
Operand3		S				A	N	P		B						yes	no

Function

The PROCESS statement is used in conjunction with Entire System Server. Entire System Server allows you to use various operating system facilities such as reading and writing files, VTOC and catalog management, JES queues, etc.

See the section Getting Started in the Entire System Server User's Guide for further information on the PROCESS statement and its individual clauses.

USING

The USING clause is used to pass parameters to the Entire System Server processor. This is done by assigning a value (*operand2*) to a field (*operand1*) in a view defined to Entire System Server. See the Entire System Server documentation for view description.

Note:

Multiple specifications of "operand1=operand2" must be separated either by the input delimiter character (as specified with the session parameter ID) or by a comma. A comma must not be used for this purpose, however, if the comma is defined as decimal character (with the session parameter DC).

GIVING

The GIVING clause is used to specify the fields (*operand3*) for which values are to be returned by the Entire System Server processor. Each field must be defined in a view used by Entire System Server.